AVAILABLE COLOURS







SI ACK



MATTE AXIS GREY METALLIC



IMPERIAL RED METALLIC

Dealer Stamp

• *The technical specifications and design of the vehicle may vary according to the requirements and conditions without any notice • New Livo meets Bharat Stage VI norms • Product shown in the picture may vary from actual product available in the market • Accessories shown in the picture are not part of standard equipment • All features may not be part of all variants.

Honda Motorcycle and Scooter India Pvt. Ltd.,

Registered Office: Commercial Complex II, Sector - 49-50, Golf Course Extension Road, Gurugram - 122018 (Haryana), India Visit us at: www.honda2wheelersindia.com Customer Care: customercare@honda2wheelersindia.com

TECHNICAL SPECIFICATIONS⁺

BODY DIMENSIONS	
Length	2020 mm
Width	Drum - 742 mm, Disc - 751 mm
Height	1116 mm
Wheel Base	1278 mm
Ground Clearance	163 mm
Kerb Weight	Drum - 113 kg, Disc - 114 kg
Seat Height	790 mm
Fuel Tank Capacity	9 L
ENGINE	
Туре	Air Cooled, 4 Stroke, SI, BS-VI Engine
Displacement	109.51 cc
Max Engine Output	6.47 KW @ 7500 rpm
Max Torque	9.30 N-m @ 5500 rpm
Fuel System	PGM-FI
Bore x Stroke (mm)	47 x 63.121
Compression Ratio	10.1:1
Starting Method	Self/Kick
TRANSMISSION	
Clutch Type	Multiplate Wet Clutch
No. of Gears	4 Gear
TYRES & BRAKES	
Tyre Size & Type (Front)	80/100-18 M/C 47P, Tubeless
Tyre Size & Type (Rear)	80/100-18 M/C 54P, Tubeless
Brake Type & Size (Front)	Disc - 240 mm, Drum - 130 mm
Brake Type & Size (Rear)	Drum - 130 mm
FRAME & SUSPENSION	
Frame Type	Diamond Type
Front Suspension	Telescopic
Rear Suspension	Hydraulic Type
ELECTRICALS	
Battery	12V, 4Ah
Headlamp	Halogen Bulb, DC











CUTTING EDGE TECHNOLOGY

eSP TECHNOLOGY



PEM-FI FUEL INJECTION

PGM-FI

PGM-FI system with 8 sensors constantly injects optimum fuel and air mixture resulting in efficient combustion that aids in consistent power output and higher mileage.

SILENT START WITH ACG

Honda's unique ACG starter motor removes gear meshing noise and helps start the engine without a jolt.

FRICTION REDUCTION

The piston cooling jet reduces friction and maintains optimum engine temperature. The offset cylinder and rocker roller arm further reduces the frictional losses in the engine.



URBAN STYLE



EDGY FRONT LOOK

Always arrive in style with the unique combination of a muscular shroud, chiseled visor, sharp headlight, and detailed air duct design.



STRONG REAR APPEARANCE

Leave a strong impression with an excitingly designed tail-light and grab rail.



MUSCULAR TANK DESIGN
WITH STRIKING GRAPHICS
A definite head-turner, the
muscular fuel tank design
with edgy graphics makes it very appealing.

DIGITAL ANALOGUE METER

Get all the ride information in style with precision.



COMFORT AND CONVENIENCE



C HEADLAMP

The DC Headlamp gives consistent illumination while riding irrespective of the speed and riding conditions.



SIDE STAND ENGINE CUT OFF

Adds to the safety of the rider, it cuts off the ignition if the vehicle is put in gear when the side stand is engaged.



ENGINE START/STOP SWITCH

Start and stop your bike with just the flick of a switch anytime anywhere. Enjoy enhanced convenience.



5-STEP ADJUSTABLE REAR SUSPENSION

Make your ride comfortable with 5-Step Adjustable Rear Suspension on all road conditions.



SERVICE DUE INDICATOR

Want to keep your Livo in the best condition all the time? No problem. Service due indicator on the meter console will give a reminder, even if you forget.



CBS WITH EQUALIZER

The Equalizer Technology in Combi Brake System distributes optimal braking force between front and rear wheels ensuring shorter braking distance with rock-solid balance.



LONG AND COMFORTABLE SEAT

Makes every ride comfortable for the rider and pillion, despite the conditions of the road.



INTEGRATED HEADLAMP BEAM & PASSING SWITCH

Integrated Smart Single Switch for passing signal and low/high beam.