## **TECHNICAL SPECIFICATIONS**

	PARAMETERS	MEASUREMENTS
BODY DIMENSIONS	Length	2061 mm
	Width	786 mm
	Height	1113 mm
	Wheel base	1347 mm
	Ground clearance	177 mm
	Kerb weight	Single Disc: 139 kg   Double Disc: 141 kg
	Seat length	594 mm
	Seat height	796 mm
	Fuel tank capacity	12L
ENGINE	Туре	4 Stroke, SI Engine
	Displacement	162.71cc
	Max engine output	9.9kW @7500 rpm
	Max torque	14.58 N-m @5500 rpm
	Fuel system	PGM FI
	Bore x stroke	57.300 x 63.096
	Compression ratio	10.0:1
	Starting method	Self/Kick
TRANSMISSION	Clutch type	Multiplate Wet Clutch
	No. of gears	5
TYRES & BRAKES	Tyre size & type (front)	80/100-17M/C 46P
	Tyre size & type (rear)	150/70-17M/C 62P
	Brake type & size (front)	Disc-276 mm
	Brake type & size (rear)	Disc-220 mm, Drum-130 mm
FRAME & SUSPENSION	Frame type	Diamond
	Front suspension	Telescopic
	Rear suspension	Monoshock
ELECTRICALS	Battery	12V, 4.0Ah
	Head lamp	LED

- +The technical specifications and design of the vehicle may vary according to the requirements and conditions without any notice.
  SP 160 meets Bharat Stage VI norms.
- Products shown in the picture may vary from the actual product available in the market.
  Accessories shown in the picture are not part of standard equipment.
- Conditions apply.



Honda Motorcycle and Scooter India Pvt. Ltd.

Registered Office: Plot No.1, Sector-03, IMT Manesar, Distt. Gurugram-122050 (Haryana)
Tel: +91(0)124-2290011, +91(0)6712800, Fax: +91(0)124-6712999

HONDA Visit us at: www.honda2wheelersindia.com Customer Care: customercare@honda2wheelersindia.com

Dealer Stamp



















